

Amendments to the Specification:

Please replace paragraph [0030] with the following amended paragraph

[0030] Inserts 33a and 33b include a wedge shaped body 35 including a semicircular extension 36 which snugly engages the semicircular upper wall 37 of takeout jaws bodies 34a and 34b. Each insert 33a and 33b also includes an extension 38 which inserts into a corresponding aperture 39 of the associated takeout jaw body 34, as shown in the rear perspective view of FIGURE 3B. Inserts 33a and 33b further include an elongated male extension ~~or detente (not shown)~~ 40 (See FIGURE ~~3B~~ 3E for the elongated male extension 40) which engages a corresponding elongated female depression 41 in takeout jaw body 34 when extension 38 of the given insert 33a or 33b is inserted into aperture 39 of the associated takeout jaw body 34.

Please replace paragraph [0033] with the following amended paragraph

[0033] In particular, upper wall 37 of body 34 is thinnest at the distal points 46a- 46b on the semicircle and thickest at the center point 47 of the semicircle. Semicircular lower wall 48 of semicircular body 37 is substantially flat. Therefore, sloped surface 45 and flat surface ~~58~~ 48 are spaced apart vertically, to define a wedge - shaped slot which snugly receives corresponding sloped and flat surfaces of the associated wedge - shaped insert 33.